DS-2CC12D9T-(A)
HD1080P WDR Box Camera





主要特色色

- 2 百萬畫素高清解析度
- 類比高清 1080P 影像輸出
- 日夜自動切換
- OSD 控制選單，3D 數位雜訊抑制
- 120dB 真實寬動態（WDR）
- AC 24V / DC 12V(-A)
- 同軸電纜傳輸訊號（HIKVISION–C）


產品規格

攝影機	
感光元件	2MP CMOS Image Sensor
訊號制式	PAL/NTSC
有效畫素	1944 (H) x 1092 (V)
最低照度	0.003 Lux (F1.2, 自動增益開啟)，紅外線啟用：0 Lux
快門速度	1/30 ~ 1/50, 000 秒
鏡頭安裝	C/CS mount
自動光圈	DC 驅動
日夜切換	紅外線濾光片自動切換
同步	內部同步掃描
寬動態（WDR)	120dB 真實寬動態
影像張數	1080P @ 30fps
影像輸出	1 x 類比高清輸出
CVBS 輸出	1Vp-p BNC 輸出（75Ω/BNC)
警報	-A: 1 x 警報輸入; 1 x 警報輸出
訊號雜訊比	＞62dB
選單	
場景模式	室內 / 戶外 / 室內 1 / 微光
攝影機名稱	開啟 / 關閉 (15 個字元，顯示位置可以移動)
自動增益（AGC)	支援
日夜切換模式	彩色 / 黑白 / EXT
白平衡	自動 / 手動 / AWC-SET
隱私遮罩	開啟 / 關閉，最多可設定 8 個區域
位移偵測	開啟 / 關閉，最多可設定 4 個區域
背光補償（BLC)	支援
防閃爍	開啟 / 關閉
語言	繁中 / 英文
功能	強光抑制 / 背光補償 / 數位降噪 / 數位變焦（62X) / 慢速快門 / 鏡像 / 除霧 / 異常畫素修正 / 智慧數位變焦 / 鏡頭陰影校正
General	
工作溫度/濕度	溫度: -30 ˚C ~ 60 ˚C (-40 ˚F ~ 140 ˚F)、濕度: 90% 以下
電源	DC 12V±15%, -A: AC 24V±15%, DC 12V±15%
耗電量	Max. 4W, -A: Max. 6W
通訊協議	同軸控制，HIKVISION-C (TVI 格式)
外型尺寸	69.2 × 57.3 × 148.7mm (2.7” × 2.3” × 5.85”)
重量	520 g

產品型號

DS-2CC12D9T-(A)

外型尺寸



配件



DS-1292ZJ

Wall Mounting



DS-1332HZ

Indoor Housing



DS-1331

Outdoor Housing



DS-1H18

Video Balun



X41T

Camera Tester



DS-1330HZ

Indoor Housing



TV0309D-MPIR

Manual Focusing 3MP IR Lens



DS-1299ZJ

Pendant Mounting

Distributed by

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

© Hikvision Digital Technology Co., Ltd. 2015 | Data subject to change without notice |