

PS-40848

八埠超高速智慧網管型網路供電交換器



固定端口	2 個 10/100/1000M RJ45 PORT
	8 組千兆 SFP
指示燈號	PWR 電源, SYS 系統, 1~8Port, 9~10 UPIINK
交換內容	32 Gbps 無阻塞
轉發率	14.44Mpps
MAC	8K
封包緩衝區	4.1M
傳輸方式	存儲轉發
端口特性	10/100/1000M 自動偵測 MDI/MDI-X 全雙工自動偵測
雙絞線特性	10MBASE-T cat 3.4.5 UTP (250M) 100 MBASE-T cat 5 UTP (100M) 100 MBASE-T cat 6 UTP (1000M) 單模單纖最大傳輸距 20KM 單模雙纖最大傳輸距 20KM 多模雙纖最大傳輸距離 850/2KM 可選配 3-80KM 光模塊
工作溫度	-10°C~55°C
儲存溫度	-40°C~70°C
工作濕度	10%~90%無凝結
儲存濕度	5%~95%無凝結
防雷等級	3KV 8/20us
防護等級	IP30

裸機尺寸	225(L)*105(W)*35(H)mm
輸入電壓	DC 12V2A
認證	CE ,FCC part 15 classB , CE/LVD EN60950
整機功耗	15W
變壓器電壓	110-240V 50/60Hz

FIBER MODULE LIST

	Model	Description	Unit
1.25G Fiber Module	850MM-LC	1.25G SFP module, dual LC interface. Multi mode dual fiber, 850nm. Transmission distance is 550meters. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1310SM-LC	1.25G SFP module, dual LC interface. Single mode dual fiber, 1310nm. Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315A-LC	1.25G SFP module, single LC interface. Single mode single fiber, 1310nm(transmitter), 1550nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315B-LC	1.25G SFP module, single LC interface. Single mode single fiber, 1550nm(transmitter), 1310nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315A-SC	1.25G SFP module, single SC interface. Single mode single fiber, 1310nm(transmitter), 1550nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315B-SC	1.25G SFP module, single SC interface. Single mode single fiber, 1550nm(transmitter), 1310nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
Ethernet Module	SFP/TP	1.25G Ethernet module , cover SFP to 10/100/1000M RJ45 port	PC